

LR-60

Low-Mid Rise Lifts

SKU# 5175729

6,000-lb. Capacity / Low-Rise Lift

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

BendPak's Low-Rise Lifts are Your Solution for Quick Service

When you need a [low-rise lift](#) to add versatility and productivity to your shop or garage, your first stop should always be BendPak. Simple, safe and rugged, this rubber-topped low rise lift can handle a mighty 6,000-lb. load without hogging your precious floor space. Plus, it happily fits into narrower bays. The LR-60 is the ideal solution for quick service on today's passenger cars and light trucks. With wide rubber pads, wheel service and auto-body repair can now be performed on a surprisingly large variety of vehicles.



Features

- Portable version available
- Electric / hydraulic power system
- Multi-position safety locks
- Rubber lifting blocks included
- Dropped cross bar for added clearance
- Heavy-duty steel channel frame

Specifications

Lifting Capacity	6,000 lbs. (2,724 kg)
Lifting Cap. (Front)	3,000 lbs. (1,361 kg)
Lifting Cap. (Rear)	3,000 lbs. (1,361 kg)
Lift Height	26" (660 mm)
Lift Height + Blocks	27.5" (699 mm)
Lift Height + Optl. 3" Blocks	29" (737 mm)
Overall Pad Length	53" (1,346 mm)
Overall Length	82" (2,083 mm)
Overall Width	70.5" (1,791 mm)
Lowered Height	4" (102 mm)
Lifting Time	35 sec
Motor (*)	115/208-230 VAC / 50-60 Hz / 1 Ph
Lift Pad Dimensions	18" x 52" (457 mm x 2,591 mm)
Shipping Weight	814 lbs. (370 kg)
Shipping Dimensions	82" x 70" x 20" (2,083 mm x 1,778 mm x 508 mm)

* Motor is dual voltage, but will be shipped wired low voltage. If 208-230 VAC operation is required, the motor will have to be re-wired according to the wiring diagram found on the motor data plate. Special voltages available upon request. The design, material and specifications are subject to change without notice.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.