

# PL-6KDT

## Parking Lifts

SKU# 5175157

12,000-lb. Cap. Parking Lift / Tandem / Independent Platforms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## Safely Converts Your Two-Car Garage into a Four-Car Garage

The PL-6KDT is an indoor-outdoor tandem-style [parking lift](#) that holds a total of four vehicles in its 236.5" x 211" x 123.75" frame. Dual hydraulic cylinders and a pair of stabilizing lifting cables support two lifting platforms. The cables are routed internally throughout the parking lift.

This lift is intended for use by anyone with four vehicles and a wide garage area to store them. You'll be surprised to see how well this unit fits in a variety of garage sizes. In the right space, it can be successfully utilized for commercial or residential purposes.

## Features

- 6,000-lb. capacity per deck
- Perfect for cars, light trucks, motorcycles and ATVs
- Rugged I-beam and C-channel construction
- Built-in wheel stops
- Wide base-plate for maximum stability
- Front and rear wheel chocks
- Superstructure features durable powder-coat finish
- Dual hydraulic cylinders with heavy-duty steel lifting cable
- Heavy-duty steel construction
- Reliable electric-hydraulic power system
- Full-width platform to keep bottom vehicles protected
- Simple controls
- Oversized sheave diameter reduces cable fatigue
- High-speed lifting
- Features heavy-duty 3/8" aircraft cable
- Rugged 1.25" roller axles
- Multi-position safety locks in each column
- Runways feature non-skid surface
- Push-button pneumatic safety release
- Independent backup slack-cable safety latches
- Customizable power unit location



## Specifications

<b>Lifting Capacity</b>	6,000 lbs. (2,722 kg)
<b>Overall Width</b>	211" (5,352 mm)
<b>Overall Length</b>	236.5" (6,008 mm)
<b>Overall Height</b>	123.75" (3,140 mm)
<b>Min. Runway Height</b>	9" (230 mm)
<b>Max. Rise</b>	89" (2,261 mm)
<b>Width Between Posts</b>	185.5" (4,715 mm)
<b>Platform Width</b>	82" (2,086 mm)
<b>Platform Length</b>	152" (3,862 mm)
<b>Drive-thru Clearance</b>	93" (2,374 mm)
<b>Locking Positions</b>	1 / Adjustable
<b>Lifting Time</b>	30 sec
<b>Standard Motor</b>	220 VAC / 60 Hz / 1Ph

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult [www.autolift.org](http://www.autolift.org) for complete listings or contact BendPak via [contact@bendpak.com](mailto:contact@bendpak.com).