

You get it all



The QuickJack portable lifting system makes vehicle maintenance on and off the track convenient and lightning fast. The QuickJack can go anywhere and is easily stowed in the trunk or back seat of most cars. Bring it to the track, or drop it on your garage floor to perform routine maintenance in the comfort of your home, all in seconds.



The QuickJack replaces clumsy floor jacks and unstable jack stands with a safe, durable and convenient vehicle jacking and support system. Simply position the lightweight jack frames under the vehicle, push the raise button on the hand-held pendant control, and in seconds the entire car is about 21" off the ground, ready for tire changes, chassis tuning or other maintenance.

The ruggedly built frames collapse to a low three-inch profile, so they fit where other jacks and lifts don't. With QuickJack, practicality and portability become reality. Because the QuickJack is void of any cross members, it provides total undercar access and can be installed at a width that best suits the vehicle being raised.

Call 1-888-262-3880 or visit www.quickjack.com

QUICKJACK™

The Ultimate Portable Car Lift

- Sets up in seconds
- Safe and durable
- Easy to use
- Portable



4 WEIGHT CAPACITIES
 3,500 • 5,000 • 6,000 • 7,000 lbs.



6 MODELS TO CHOOSE FROM

Specifications:

| | BL-3500SLX | BL-5000SLX | BL-5000EXT | BL-7000SLX | BL-7000EXT | BL-6000XLT |
|---------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Lifting capacity | 3,500 lbs. (1,588 kg) | 5,000 lbs. (2,268 kg) | 5,000 lbs. (2,268 kg) | 7,000 lbs. (3,175 kg) | 7,000 lbs. (3,175 kg) | 6,000 lbs. (2,722 kg) |
| Lowered height | 3" (76 mm) | 3" (76 mm) | 3" (76 mm) | 3.5" (89 mm) | 3.5" (89 mm) | 3.5" (89 mm) |
| Lifting height (frame only) | 16.5" (419 mm) | 17.5" (445 mm) | 17.5" (445 mm) | 18" (457 mm) | 18" (457 mm) | 18" (457 mm) |
| Lifting height (stacked blocks) | 20" (508 mm) | 21" (533 mm) | 21" (533 mm) | 21.25" (540 mm) | 21.25" (540 mm) | 21.25" (540 mm) |
| Lift point spread (min.) | 27" (686 mm) | 31.5" (800 mm) | 37.5" (953 mm) | 31.5" (800 mm) | 37.5" (953 mm) | 47.5" (1,207 mm) |
| Lift point spread (max.) | 50.5" (1,283 mm) | 60" (1,524 mm) | 66" (1,676 mm) | 60" (1,524 mm) | 66" (1,676 mm) | 76" (1,930 mm) |
| Frame width | 10.5" (267 mm) | 11" (278 mm) | 11" (278 mm) | 12.5" (318 mm) | 12.5" (318 mm) | 12.5" (318 mm) |
| Frame length | 62.5" (1,588 mm) | 70" (1,778 mm) | 76.5" (1,940 mm) | 70" (1,778 mm) | 76.5" (1,940 mm) | 86.5" (2,197 mm) |
| Frame weight | 60 lbs. (27 kg) | 76 lbs. (35 kg) | 80 lbs. (36 kg) | 96 lbs. (44 kg) | 101 lbs. (46 kg) | 110 lbs. (50 kg) |

Optional Accessories

SUV & Light Truck Adapter Kit

- (4) Contact pads
- (4) Sliding receivers
- (4) 3" Stackable adapters



SLX Frame Extension Kit

- (2) Frame extension adapters with 66" lift point spread each
- Rugged 14-gauge steel construction
- Easy to carry
- Fits 5000/7000SLX models



(Rubber Blocks NOT included)

ATV / Motorcycle Lift Adapter Kit

- Heavy-duty tie-down rings
- Aluminum diamond tread plate
- Adjustable wheel clamp



(Compatible with all models except BL-6000XLT)

Motorcycle Lift Adapter Kit



- Tie-down rings
- Lightweight platform
- Adjustable wheel clamp
- Easy installation

(Motorcycle Jack not included)

QUICKJACK™