

# R76ATR



## Tire Changer

SKU# 5140140

Tilt Back, Right-Tower Single Assist, 30" Capacity, 220V, 3-Phase, 50/60hz

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

## Tilt-Tower Tire Changer Design for a Smaller Footprint

The Ranger R76ATR [tire changer](#) is easy to operate, rugged enough to stand up to demanding workloads and comes equipped with power assist tower tools to help when mounting low-profile performance tires. A large 30" capacity turntable features adjustable, hardened-steel RimGuard™ wheel clamps. These provide an internal clamping capacity of 9"- 28" and external clamping capacity of 10"- 30".

## Specifications

<b>Motor</b>	3 HP (220 VAC 50-60 HZ)
<b>Drive System Type</b>	Electric / Hydraulic
<b>Air Requirement</b>	110-175 PSI (8-12 BAR)
<b>Wheel Clamping Method</b>	4 Clamps - Internal / External
<b>Table Clamping System</b>	Dual Pneumatic Cylinders
<b>Bead Breaking System</b>	Adjustable Pneumatic Blade
<b>Tower Design</b>	Tilt-Back
<b>Power Assist Tower(s)</b>	Single / Right-Side
<b>Bead Lifting Roller(s)</b>	Single / Right-Side
<b>Upper Bead Assist Roller</b>	Single / Right-Side
<b>Vertical Shaft / Tool Head</b>	Pneumatic / Locking
<b>Powerful Bead Seating System</b>	TurboBlast™
<b>Internal Rim Clamping Capacity</b>	10" - 30" (254 mm - 762 mm)
<b>External Rim Clamping Capacity</b>	9" - 28" (229 mm - 711 mm)
<b>Turntable Tire Width Capacity (Mounting)</b>	4" - 18" (102 mm - 457 mm)
<b>Bead Breaker Tire Width Capacity (Demounting)</b>	1.5" - 16" (38 mm - 406 mm)
<b>Maximum Tire Diameter</b>	43" (1,092 mm)
<b>Shipping Weight</b>	970 lbs. (440 kg)



## Standard Features

- Traveling Drop-Center Hold Down Device
- Inflation System
- Inflation Gauge & Air Dump Valve
- Inflation Pressure Regulator/Limiter
- Oiler / Lubricator
- Air Regulator
- Bead Tool/Tire Iron
- Alloy-Steel Mount-Demount Head
- Nylon Mount-Demount Head
- Large Soap Bucket
- Soap Brush