LiftMotive

AMGO A268C Extreme Duty Two Post Lift

6800KG Lifting Capacity Electro Hydraulic, Direct Drive, Clear floor



Featuring an extra-tall design with 3-in-1 height setting technology.



Specially designed for trucks, vans, campers, buses, and other larger vehicles.



Frame Cradle Pads for Trucks & SUVs and Screw pads (included)

┱



Certificate No.: CE-MC-210519-027-30-5A - CCQS Ireland EN 1493:2010 Vehicle Lifts / EN ISO 12100:2010 / EN 60204-1-2018



75mm & 150mm Extension adapters (included)




Heavy Duty Two-Stage arms



Electronic Control system including manual single point safety release

	: E		
В		A	
		┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣ ┣	



Measurement	Dimension
A - Lift height without extension	1912 - 1946mm
A - Lift Height with extension	2141 - 2175mm
A - Lock height without extension	1862 - 1896mm
A - Lock height with extension	2091 - 2125mm
B - Overall Height (3 options)	4420/4725/5030mm
C - Overall Width	3829mm
D - Drive-Thru Clearance	2787mm
E - Width Between the Columns	3137mm
F - Minimum Pad Height	173mm
Arm reach Min / Max	1094-1686mm
Voltage / Motor	400V / 3.0HP
Gross Weight	1182KG

LiftMotive Europe B.V. - Melkweg 16A, 1841JJ Stompetoren www.liftmotive.com | info@liftmotive.com | Tel. +31 627365781