




Optional: 2800KG Low Profile Rolling Bridge Jack (pneumatic hydraulic)




Optional: LED Light kits made from aluminium PCB.




Certificate No.: CE-MC-210519-027-04-5A - CCQS Ireland  
EN 1493:2010 Vehicle Lifts / EN ISO 12100:2010 / EN 60204-1:2018



24-Volt Automatic control system with mechanical self-locking and air-release safety lock system.



Optional platform extension kits add 660mm length to the runways.



Adjustable runway: The off-side runway can be installed with a narrower or wider positioning.

Measurement	Dimension	Measurement	Dimension
A - Overall Length (Inc. Ramps)	5512mm	H - Max Lift Clearance	1730mm
B - Overall Length ( Without Ramps)	4600mm	H - Max Lock Clearance	1660mm
C - Overall Width	3208mm	I- Drive Through Width	2498mm
D - Width Between the Columns	2852mm	J - Width between runway	85mm - 1300mm
E - Max Lifting Height	1870mm	K - Outside edge of runways	1101mm - 2316mm
E - Max Locking Height	1800mm	Lifting Capacity	4000KG
F - Overall Height	2185mm	Voltage / Motor	230V or 400V, 3HP
G - Min. Height	170mm	Gross Weight	921KG

